

3378 - Turbo Canvas Solvent 370



www.e-commerce.diateccl.es

satin 3378 - 370 g/m²

Satin coated canvas with a 1:1 weave structure for solvent inks. Due to the special coating, the Turbo canvas is suitable for heavy ink loads and uniform prints, even in critical dark tones: with optimised ink fixation. The coated surface is water-repellent and offers a good light-stability.

Advantages:

- ✓ Best buy
- ✓ Flexible finishing for ideal performance during stretching process
- ✓ Real cotton/polyester canvas (1:1 structure)
- ✓ Waterproof



Applications:

- Indoor Short-Term Promotions: In-house advertising for e.g. promotion at concerts, theatres, cinemas or shopping malls.
- Framed Art: "Reproduction or creation of new works of art", like digital airbrush.

Ink Compatibilities:

- Latex Ink: infra red curing ink, e.g. Latex ink as used in the HP DJ L65500, which adheres to most flat and clean surfaces. Process needs heat resistant media, which does not shrink during the print cycle.
- Solvent Ink: solvent based pigmented or mild solvent based ink, which is used on printer systems like Epson, HP, Mutoh, Mikami, Océ, Roland ect.
- UV Curable Ink: special UV curable ink which is suitable on most surfaces.
- Eco Solvent:

Properties:

- Quick dry: The special coating effects that ink will be absorbed in a fraction of a second therefore applications can follow directly after printing.
- Waterresistency/Waterfastness: this product printed with pigmented based inks can be used for short-term outdoor applications without any laminate film (see referring data sheet and recommendations of use). That means this product withstands rain and other outdoor influences, but water droplets can cause slight differences in color density within colored areas.
- Structure: A real textile base material.

Physical Properties:

Total Weight	370 g/m ²	ISO 536
Thickness	470 micron	ISO 534
Whiteness	75 %	

Last update: 31/12/2021

TEXTILE MEDIA
I - 38023 CLES (TN)
Via Campo Sportivo, 24
Tel. +39 0463 421592
Fax +39 0463 422214
diatecx.textile@diatecgroup.com

GRAPHIC ARTS MEDIA
I - 38023 CLES (TN)
Zona Industriale, 126
Tel. +39 0463 422222
Fax +39 0463 422173
diatecx.graphic@diatecgroup.com

FILIALE NORD EST
I - 36051 CREAZZO (VI)
Via Piazzon, 10
Tel. +39 0444 522022
Fax +39 0444 340100
diatecx.vicenza@diatecgroup.com

FILIALE EMILIA ROMAGNA
I - 41012 CARPI (MO)
Via della Chimica, 10712
Tel. +39 059 643661
Fax +39 059 698572
diatecx.carpi@diatecgroup.com

FILIALE CENTRO SUD
I - 50053 EMPOLI (FI)
Via 1° Maggio, 57/59
Tel. +39 0571 930071
Fax +39 0571 930082
diatecx.empoli@diatecgroup.com

3378 - Turbo Canvas Solvent 370

Gloss (60°)

5 %

ISO 2813

Conditions:

- Keep the product in the original packaging (cardboard box and PE bag)
- It is always recommended that cotton gloves be used when handling InkJet coated materials to avoid fingerprints
- The converting and storage should take place in a climate from 35 to 65% to relative humidity at a temperature from 10 to 30°C.

Table of the supported printers:

See the legend below for the quality column.

Printer	Ink	Quality
Hewlett PackardDJ 8000S / 9000S / 10000S	Eco Solvent	★★
Hewlett PackardDJ L65500 Latex ink	Latex Ink	★★
Hewlett PackardDJ L25500 / 26500 Latex ink - Latex 260/280	Latex Ink	★★
Hewlett PackardScitex LX 600	Latex Ink	★★
Hewlett PackardScitex LX 800/ LX820/ LX850	Latex Ink	★★
EpsonStylus Pro GS6000 UltraChrome GS	Eco Solvent	★★★★
RolandVersaCamm VP-300i / VP-540i	Eco Solvent	★★★★
RolandVersaCamm SP-300i / SP-540i	Eco Solvent	★★★★
RolandSolJet SJ540 / SC540 SJ 740 / SC740	Eco Solvent	★★★★
RolandVS 540 / VS 640	Eco Solvent	★★★★
MimakiJV 33 / JV 34 - 260	Eco Solvent	★★★★
MutohValueJet 1204 / 1304 / 1614	Eco Solvent	★★
Zünd UVjet 215 C	UV Curable Ink	★★
swissQprint Oryx	UV Curable Ink	★★★★
swissQprint Impala	UV Curable Ink	★★★★
MimakiJV400SUV Serie		★★★★

Legend

★★★★ High

★★ Medium

★ Low

Last update: 31/12/2021

TEXTILE MEDIA
I - 38023 CLES (TN)
Via Campo Sportivo, 24
Tel. +39 0463 421592
Fax +39 0463 422214
diatec.textile@diatecgroup.com

GRAPHIC ARTS MEDIA
I - 38023 CLES (TN)
Zona Industriale, 126
Tel. +39 0463 422222
Fax +39 0463 422173
diatec.graphic@diatecgroup.com

FILIALE NORD EST
I - 36051 CREAZZO (VI)
Via Piazzon, 10
Tel. +39 0444 522022
Fax +39 0444 340100
diatec.vicenza@diatecgroup.com

FILIALE EMILIA ROMAGNA
I - 41012 CARPI (MO)
Via della Chimica, 10712
Tel. +39 059 643661
Fax +39 059 698572
diatec.carpi@diatecgroup.com

FILIALE CENTRO SUD
I - 50053 EMPOLI (FI)
Via 1° Maggio, 57/59
Tel. +39 0571 930071
Fax +39 0571 930082
diatec.empoli@diatecgroup.com